

CDD10-15 Electric Stacker Technical Specification				
Model	CDD15 (three stage mast)			
Load capacity (kg)	1500			
Load capacity on Max. height(kg)	800	700	550	400
The max. lifting height(mm)	4000	4600	5000	5500
Load center distance(mm)	600			
Fork length(mm)	1150			
Single fork width(mm)	180			
Overall fork width(mm)	695			
Lowered fork height(mm)	86			
Fixed leg length(mm)	875			
Single fixed leg width(mm)	124			
Inside width between fixed legs(mm)	391			
Outside width between fixed legs(mm)	639			
Aisle width for pallets 1000x1200 cross ways	2396			
Aisle width for pallets 800x1200 length ways	2458			
Turning radius(mm)	1620			
Front wheel size, number	φ80×70、 4 pcs			
Driving wheel size, number	φ250×80、 1 pce			
Balance wheel size, number	φ150×58、 2 pcs			
Overall length(with Pedal)(mm)	1984(2384)			
Overall width(mm)	1050			
Extended mast height(mm)	4500	5100	5500	6000
Lowered mast height (mm)	1898	2098	2232	2398
Battery voltage(dimensions)mm	24V/280Ah(1010/212/465)			
The charger	24V/40A			
Lifting Motor	3.0kw. Liftspeed,laden/unladen:116/74mm,			
Driving Motor	AC;1.2kw. Driving speed:laden/unladen:4.8/3.4km/h			
Working time of fully charged batteries (h)	5			
Service Weight(kg)	1365	1410	1440	1510

